



" " " , . - , , .14.  
/ : 8(812)329-69-30  
974-80-60  
: info@hydrotrade.ru  
www.hydrotrade.ru

Бесшовные холоднотянутые трубы для гидроцилиндров  
DIN 2391 NBK

**Seamless cold drawn cylindertube according DIN 2391**  
**NBK normalised, honed or rolled ID H8, with certificate according to 3.1C**  
**Impacttest min. 27J at -20 C, hard die stamped** articlecode: **1215220**

**According to:**

Material : H8 - St. 52.0 NBK  
Outside diameter : DIN 2391  
Inside diameter : honed or skived + roller burnished with H8 tolerance  
Lenghts : deliveries in commercial lengths, or fixed lengths on request  
during the cutting there is a possibilty that tube-ends slightly ovalise

**Mechanical properties**

Yieldstrength : 500-650 N/mm<sup>2</sup>  
Tensile strength :  $\geq 355$  N/mm<sup>2</sup>  
Elongation (A5) :  $\geq 21$  %  
Impacttest : 27 Joule / -20 C



198096, . " " " ,  
 . / : 8(812)329-69-30 , .14.  
 974-80-60  
 . : info@hydrotrade.ru  
 www.hydrotrade.ru

	Inside mm	Wallthickness mm	Outside mm	Kg/m	Int. pressure in bar	articlecode 1215220
<b>Бесшовные холоднотянутые трубы для гидроцилиндров            DIN 2391 NBK</b>	80	10	100	22,18	320	
	90	10	110	24,65	290	
	100	12,5	125	34,68	333	
	* 120	15	150	49,94	320	
	125	15	155	51,76	309	
	* 140	15	170	57,31	282	
	* 200	22,5	245	123,45	293	
	Other sizes on request					